

Mounting Kits for Valves, ISO5211

- Mounting Kits for ball, plug and butterfly valves with a Mounting Flange according to ISO 5211
- The Kit consists of Mounting Bracket, coupling and bolts




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

DIMENSIONS (mm)

Fig.	Interface Drilling		A1	A2	B	C	Material	Part no. (*)
	Top	Bottom						
1	F10-F12	F10-F12	127	–	126	157	Steel, zink plated	12932
2	F10-F12-F14	F10-F12-F14	127	–	80	157	Steel, zink plated	807109
3	F07	F07-F10	87	72	60	100	Stainless Steel	12764
4	F07-F10	F10-F12	110	87	70	140	Stainless Steel	12686
5	F04-F05	F05	48	–	40	100	Stainless Steel	807105
6	F03-F04-F05	F04-F05	48	–	40	100	Stainless Steel	12314-2
7	F05	F07	68	48	40	100	Stainless Steel	12312

(*) Complete Mounting Kit, including coupling and bolts.

Additional drilling at Mounting Brackets corresponding to extra drilling at actuators Type 1, see page 2.

Mounting Kits for Valves, ISO5211

Additional drilling at Mounting Brackets corresponding to extra drilling at actuators Type 1.

ADDITIONAL DRILLING, one side




Fig. 1 (top view)




Fig. 4 (bottom view)




Fig. 5 (bottom view)




Fig. 6 (bottom view)




Fig. 7 (bottom view)

ADDITIONAL DRILLING, two sides




Fig. 2 (bottom view)




Fig. 3 (bottom view)

DIMENSIONS (mm)

Fig.	E x F	Ø	Actuator size	Notes	Part no.
1	107 x 49	6,5	12-20		12932
2	107 x 49	6,5	12-20	Same drilling top/bottom	807109
3	73 x 32	6,5	2-8	Same drilling top/bottom	12764
4	107 x 49	6,5	12-20		12686
5	73 x 32	6,5	2-8		807105
6	73 x 32	6,5	2-8		12314-2
7	73 x 32	6,5	2-8		12312